

Solargiga Energy

MONO-CRYSTALLINE CONVENTIONAL HALF-CUT MODULE

JMPV-T1/66-660~670(R)

Maximum Power

670W

Maximum Efficiency

21.57%

Power Tolerance

0~+5W



CELL TYPE

P Type/G12/PERC/12BB/Half-Cell



HIGH EFFICIENCY, HIGH GENERATION

Based on 210mm wafer, more uniform current collection capability, Half-Cell design reduces internal current and internal loss and improves output of module power.



EXCELLENT ANTI-PID PERFORMANCE

All products have excellent anti-PID performance to ensure module's stable power output.



SUPPORT 1500V SYSTEM

Increase the number of system modules in series, reduce overall cost of terminal power plant.



STRONG MECHANICAL LOAD CAPACITY

Withstand snow pressure up to 5400Pa on the front face and wind pressure up to 2400Pa on the rear face.

IEC61215/ IEC 61730

IEC62804 : Anti-PID Test


IEC61701 : Salt Spray Test

IEC62716 : Ammonia Corrosion Test

IEC60068-2-68: Dust and Sand Test

12 YEARS Product Warranty

25 YEARS Power Output Warranty



Solargiga Energy

Founded in 2000 , Solargiga Energy Holdings Limited ('Solargiga Energy' , HKEX:00757.HK), is a renewable energy company which combines the business of the whole mono-crystalline industrial chain covering R&D manufacturing , photovoltaic application and global marketing . It 's committed to provide PV products, technical support and integrated system solution for global customers.

MBB MONO-CRYSTALLINE CONVENTIONAL HALF-CUT MODULE

JMPV-T1/66-660~670(R)

MODEL NUMBER	JMPV-T1/66-660~670(R)		
ELECTRICAL PARAMETERS (STC)			
Max Power (Pmax/W)	660	665	670
Max Power Voltage(Vmp/V)	37.83	37.96	38.12
Max Power Current (Imp/A)	17.45	17.52	17.58
Open Circuit Voltage(Voc/V)	45.42	45.58	45.75
Short Circuit Current (Isc/A)	18.52	18.59	18.66
Module Efficiency (%)	21.25	21.41	21.57

STC(Standard Test Condition): AM1.5, Irradiance 1000W/m², Cell Temperature 25°C

ELECTRICAL PARAMETERS (NMOT)			
Max Power (Pmax/W)	495.05	498.85	502.39
Max Power Voltage(Vmp/V)	35.26	35.38	35.53
Max Power Current (Imp/A)	14.04	14.10	14.14
Open Circuit Voltage(Voc/V)	43.05	43.20	43.36
Short Circuit Current (Isc/A)	15.02	15.07	15.13

NMOT(Nominal Module Operating Temperature): Irradiance 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

TEMPERATURE CHARACTERISTICS	
Cell Operating Temperature	42.5±2°C
Temperature Coefficient of Isc	0.044%/ °C
Temperature Coefficient of Voc	- 0.251%/ °C
Temperature Coefficient of Pmax	- 0.340%/ °C




MECHANICAL PARAMETERS	
Cell Type	P Type/G12/PERC/12BB/Half-Cell 210×105mm
Number of Cells	132 (6×11×2)
Weight	35.0±1.0kg
Dimension	2384×1303×35mm
Glass	3.2mm Tempered Coated Glass
Encapsulating Material	EVA
Frame	Anodized Aluminum
Junction Box	Protection Degree IP68
Cable	4.0 mm ² ; +/-300mm or Customized Length

OPERATING CONDITIONS	
Max System Voltage	1500V
Operating Temperature	-40°C~+85°C
Max Series Fuse Rating	30A
Front Face Static Load (snow etc)	5400Pa
Rear Face Static Load (wind etc)	2400Pa

Installation should strictly obey the installation Manual of Solargiga Energy.

PACKING INFORMATION	
31pcs/pallet	558pcs/40'HQ

*Power Test Uncertainty +/-3%



Sales HOT-line
 Domestic Sales: (86)416 508 1597
 Overseas Sales: (86)416 712 0178
 Xihai Industry Park, Economic and Technical
 Development Zone, Jinzhou, Liaoning
 Province, CHINA.

Note: Electrical parameters are only used for comparison between different types of modules. Due to product innovation, Solargiga Energy reserves the right to adjust the information in this datasheet at any time without prior notice. The technical data in this datasheet may be slightly deviated. Customer shall obtain the latest version of the datasheet when signing contract and making it an integral part of the binding contract signed by both parties.

